

CLAIMS

1. A digital camera comprising:
 - 5 - an image recording subsystem for making image recordings;
 - a location-providing subsystem for providing location data items representative of a current location of the camera,
 - a location-stamping subsystem for associating with image recordings taken using the image recording subsystem, respective location data items, provided by said location-providing subsystem, that each represent the location of the camera at the time the
10 corresponding image recording was taken, and
 - a location recording subsystem for effecting user-triggered recording, independently of the recording of an image recording, of location data items provided by the location providing subsystem, these location data items and those associated with the
15 location-stamped image recordings being recorded in a sequential association with each other.
2. A camera according to claim 1, wherein both the location-stamped image recordings and the location data items recorded independently of recording an image recording, are
20 recorded in data structures of the same form, the data structures being arranged or explicitly linked into a sequence indicative of the order of recording.
3. A camera according to claim 1, wherein each location data item recorded independently of recording an image recording, is recorded in a log distinct from the
25 location-stamped image recordings along with sequence data indicating its sequence position relative to the sequence of recorded image recordings.
4. A camera according to claim 1, wherein the image recording subsystem and the location recording subsystem have independent user-operable controls for triggering recording.
- 30 5. A camera according to claim 1, wherein the image recording subsystem and the location

recording subsystem have a common user-operable control for triggering recording and a common sensor for determining whether there is an image to be recorded, the image recording subsystem being operative to record an image recording when said control is operated only if said sensor indicates that an image is present, and the location recording
5 subsystem only recording a location data item when said control is operated, if said sensor indicates that an image is absent.

6. A camera according to claim 5, wherein said sensor is a sensor for detecting whether a lens shutter of the camera is open or closed.

10

7. A camera according to claim 5, wherein sensor is an optical sensor located in an image plane of the camera.

8. A camera according to claim 7, wherein said optical sensor is constituted by an
15 electronic image capture device of the image recording subsystem.

9. A camera according to claim 1, wherein the location providing subsystem is a GPS subsystem.

20 10. A camera according to claim 1, wherein the location providing subsystem comprises a cellular mobile radio subsystem for receiving location-related data from a mobile radio infrastructure.

25